



INSTRUCTION

(MODEL:SM-I015/200)

SUIMING

LED HIGH-BAY LIGHT

Product features

- Widely used for indoor/outdoor applications.
- High brightness SMD3030 chips with nano tech reflector, 120lm/w efficiency.
- 3D heat flow channel design. More efficient and faster to heat dissipate.
- Unique Optic reflector creates good performance light effort.
- Energy saving 80% to replace metal halide light.



Specification

Item: SM-I015/200
Power: 200W
Voltage: AC85-265V
Frequency: 50-60Hz
Light source: SMD3030 chips
Chip brand: Epistar
Chip lumens: 120lm/W
Color Temperature: 6000K
CRI: >80
PF:>0.95
Surge: 6000V
Beam angle:90°
Housing material: Die-casting aluminium
Working Temperature: -25~+40°
Diameter: ϕ 400XH150mm
IP Grade:IP66
Warranty: 3 Years



Warning Note

- Please make sure all the power is turned off before installation is completed.
- Installation must be performed by skilled technicians who are familiar with technical requirements and proper installation methods of LED luminaire.
- Working Voltage:AC85-265V 50/60Hz. Do not exceed the operating voltage range.

Application

Widely used in workshop ,factory, warehouse, parking lot, toll station, gas station,supermarket, exhibition hall, stadium, etc.

Installation

Hook Suspended Mounting

- Put the UFO high bay ring on the hook.
- Lock the hook screw, in case the lamp fall off
- Finished all the wiring.

